

Type - Tipo - Typ
Type - Tipo

P

Size - Grandezza - Grösse
Taille - Tamaño

712C


Mounting - Montaggio
Montage - Fixation
Tipo de montaje

-F

Ratio - Rapporto
Untersetzung
Reduction
Relación

6.57

Cast iron coaxial gear boxes
Riduttori coassiali in Ghisa



With IEC motor
M


With motor flange
P

2 Stages
Riduzioni
Stufen
Trains
Etapas


712C
812C
862C
1002
1102

3 Stages
Riduzioni
Stufen
Trains
Etapas


713C
813C
863C
1003
1103



Without flange / feet
-N




Output flange mounted
-F



With male input shaft
R

Modular base
B

Not available for:
862C, 1002, 1102,
1003, 1103.



Mounted feet
B..

















Feet / piedini

Feet Code	Market reference	G	H	R	L
B1	112	18	85	110	
B2	212/3	18	100	130	
S1	17	18	75	110	
S2	27	25	90		
M1	42/3	25	80		
L4	04	13	80		
L5	05	16	100		

You see feet code in the chart of the dimensions
Vedi codice piede nella tabella delle dimensioni



On request we can deliver our products according to the ATEX
A richiesta possiamo fornire i nostri prodotti secondo le normative ATEX
Auf Anfrage können wir unsere Produkte den Richtlinien ATEX entsprechend liefern
Sur demande nos produits peuvent se conformer à la réglementation ATEX
A pedido, se pueden enviar nuestros productos de acuerdo con las normas ATEX.

Output shaft Albero uscita Abtriebswelle Arbre de sortie Eje en salida	Output flange Flangia uscita Ausgangsflansch Bride de sortie Brida en salida	Motor size - Grandezza motore Motor Größe Grandeur moteur - Tamaño motor	Mounting position Posizione montaggio Einbaulage Position de montage Position de montaje	Input bore Foro entrata Eingangshohlwelle Trou d'entree Eje hueco de entrada	Terminal box position Posizione morsetteria Klemmkastenlage Position boîte à bornes Posición caja de bornes																																													
<p style="text-align: center;">I</p>  <p>→ STANDARD</p> <table border="1" data-bbox="78 649 250 1254"> <tr><td>712C 713C</td></tr> <tr><td>I → ø35</td></tr> <tr><td>L → ø38</td></tr> <tr><td>812C 813C</td></tr> <tr><td>M → ø40</td></tr> <tr><td>N → ø45</td></tr> <tr><td>862C 863C</td></tr> <tr><td>P → ø50</td></tr> <tr><td>J → ø60</td></tr> <tr><td>1002 1003</td></tr> <tr><td>J → ø60</td></tr> <tr><td>1102 1103</td></tr> <tr><td>A → ø70</td></tr> </table>	712C 713C	I → ø35	L → ø38	812C 813C	M → ø40	N → ø45	862C 863C	P → ø50	J → ø60	1002 1003	J → ø60	1102 1103	A → ø70	<p style="text-align: center;">4</p>  <p>→ STANDARD</p> <p>N Senza flangia Without flange</p> <table border="1" data-bbox="297 649 470 1254"> <tr><td>712C 713C</td></tr> <tr><td>4 → ø200</td></tr> <tr><td>5 → ø250</td></tr> <tr><td>812C 813C</td></tr> <tr><td>5 → ø250</td></tr> <tr><td>6 → ø300</td></tr> <tr><td>862C 863C</td></tr> <tr><td>6 → ø300</td></tr> <tr><td>7 → ø350</td></tr> <tr><td>1002 1003</td></tr> <tr><td>6 → ø300</td></tr> <tr><td>7 → ø350</td></tr> <tr><td>8 → ø450</td></tr> <tr><td>1102 1103</td></tr> <tr><td>7 → ø350</td></tr> <tr><td>8 → ø450</td></tr> </table>	712C 713C	4 → ø200	5 → ø250	812C 813C	5 → ø250	6 → ø300	862C 863C	6 → ø300	7 → ø350	1002 1003	6 → ø300	7 → ø350	8 → ø450	1102 1103	7 → ø350	8 → ø450	<p style="text-align: center;">-F</p> <p>Flange Flangia</p>  <p>B5</p> <ul style="list-style-type: none"> -A=56 (ø120) -B=63 (ø140) -C=71 (ø160) -D=80 (ø200) -E=90 (ø200) -F=100+112 (ø250) -G=132 (ø300) -H=160 (ø350) -I=180 (ø350) -L=200 (ø400) -CA=225 (ø450) <p>B14</p> <ul style="list-style-type: none"> -O=56 (ø80) -P=63 (ø90) -Q=71 (ø105) -R=80 (ø120) -T=90 (ø140) -U=100+112 (ø160) -V=132 (ø200) <p>Type R Tipo R</p>  <table border="1" data-bbox="705 448 878 784"> <tr><td>713C 813C</td></tr> <tr><td>-2 → ø19</td></tr> <tr><td>712C 812C 863C</td></tr> <tr><td>-3 → ø24</td></tr> <tr><td>862C 1003 1103</td></tr> <tr><td>-4 → ø28</td></tr> <tr><td>1002 1102</td></tr> <tr><td>-6 → ø42</td></tr> </table> <p>Without flange Senza flangia</p>  <p>-M → With coupling</p> <table border="1" data-bbox="705 985 878 1388"> <tr><td>713C 813C</td></tr> <tr><td>-1 → ø14 (71B5)</td></tr> <tr><td>-2 → ø19 (80B5)</td></tr> <tr><td>-3 → ø24 (90B5)</td></tr> <tr><td>712C 812C 863C</td></tr> <tr><td>-2 → ø19 (80B5)</td></tr> <tr><td>-3 → ø24 (90B5)</td></tr> <tr><td>-4 → ø28 (100B5)</td></tr> </table>	713C 813C	-2 → ø19	712C 812C 863C	-3 → ø24	862C 1003 1103	-4 → ø28	1002 1102	-6 → ø42	713C 813C	-1 → ø14 (71B5)	-2 → ø19 (80B5)	-3 → ø24 (90B5)	712C 812C 863C	-2 → ø19 (80B5)	-3 → ø24 (90B5)	-4 → ø28 (100B5)	<p style="text-align: center;">B3</p>  <p>B3 STANDARD</p>  <p>B6</p>  <p>B7</p>  <p>B8</p>  <p>V5</p>  <p>V6</p>  <p>V8</p>	<p style="text-align: center;">ST</p> <p>ST standard bore foro standard</p>	<p>With Type M specify terminal box position Con tipo M specificare posizione morsetteria</p>  <p>A</p>  <p>B STANDARD</p>  <p>C</p>  <p>D</p>
712C 713C																																																		
I → ø35																																																		
L → ø38																																																		
812C 813C																																																		
M → ø40																																																		
N → ø45																																																		
862C 863C																																																		
P → ø50																																																		
J → ø60																																																		
1002 1003																																																		
J → ø60																																																		
1102 1103																																																		
A → ø70																																																		
712C 713C																																																		
4 → ø200																																																		
5 → ø250																																																		
812C 813C																																																		
5 → ø250																																																		
6 → ø300																																																		
862C 863C																																																		
6 → ø300																																																		
7 → ø350																																																		
1002 1003																																																		
6 → ø300																																																		
7 → ø350																																																		
8 → ø450																																																		
1102 1103																																																		
7 → ø350																																																		
8 → ø450																																																		
713C 813C																																																		
-2 → ø19																																																		
712C 812C 863C																																																		
-3 → ø24																																																		
862C 1003 1103																																																		
-4 → ø28																																																		
1002 1102																																																		
-6 → ø42																																																		
713C 813C																																																		
-1 → ø14 (71B5)																																																		
-2 → ø19 (80B5)																																																		
-3 → ø24 (90B5)																																																		
712C 812C 863C																																																		
-2 → ø19 (80B5)																																																		
-3 → ø24 (90B5)																																																		
-4 → ø28 (100B5)																																																		